

SmartACU2000B



With PID



Without PID

SmartACU2000B (Smart Array Controller)

is a powerful integration of PV array communication and other smart functions. What's more, it supports 1000V/1100V/1500V DC system perfectly.

Smart

- SmartLogger2000 built-in
- Smart Anti-PID2000 module built-in (optional)
- Multiple communication interfaces including PLC, RS485, Fast Ethernet, and SFP ports, flexible applications

Simple

- Integrated communication unit with multiple functions built-in
- Easy installation with SmartLogger2000 & anti-PID module pre-assembled inside the cabinet

Reliable

- Industrial application and high reliability

Specifications	SmartACU2000B-D-PLC	SmartACU2000B-D-2PLC	SmartACU2000B-D-PID/PLC	SmartACU2000B-D-2PID/2PLC
	Configuration			
SmartLogger	SmartLogger2000			
RS485	Yes			
Number of PLC Module	1	2	1	2
Number of Smart Anti-PID2000 Module	0	0	1	2
	Environment			
Operating Temperature	-40 °C ~ +60 °C (-40 °F ~ +140 °F)			
Relative Humidity	4% ~ 100%			
Max. Operating Altitude	4,000 m (13,123 ft.)			
	Electrical			
Input AC Voltage for Cabinet	100 V ~ 240 V, L / N (L)+ PE			
Input AC Voltage for PID	380 V ~ 800 V; 3Ph+FE (Functional Earth)			
Input AC Voltage for PLC	380 V ~ 800 V; 3Ph			
Input AC Frequency	50 Hz / 60 Hz			
	Mechanical			
Cable Entries	Bottom in & out			
Maintenance	Front			
Dimensions (W / H / D)	640 x 770 x 315 mm (25.2 x 30.3 x 12.4 inch)		880 x 770 x 369 mm (34.6 x 30.3 x 14.5 inch)	
Weight	29kg (63.9 lb.)	32 kg (70.5 lb.)	49 kg (108.0 lb.)	61 kg (134.5 lb.)
Protection Grade	IP65			
Installation Options	Wall Mounting, Rack Mounting, Pole Mounting			