

# SmartACU2000B



With SmartPID2000 Module



Without SmartPID2000 Module

## SmartACU2000B (Smart Array Controller)

is a powerful integration of PV array communication and other smart functions. What's more, it supports 1000 V / 1100 V / 1500 V DC system perfectly.

### Smart

- SmartLogger2000 built-in
- SmartPID2000 module built-in (optional)
- Multiple communication interfaces including PLC, RS485, Fast Ethernet, and SFP ports, flexible applications

### Simple

- Integrated communication unit with multiple functions built-in
- Easy installation with SmartLogger2000 & SmartPID2000 module pre-assembled inside the cabinet

### Reliable

- Industrial-level application and high reliability

Technical Specifications	SmartACU2000B-D-PLC	SmartACU2000B-D-PID/PLC
<b>Configuration</b>		
SmartLogger	SmartLogger2000	
RS485	Yes	
Number of PLC Module	1	1
Number of SmartPID2000 Module	0	1
<b>Environment</b>		
Operating Temperature Range	-40°C ~ 60°C (-40°F ~ 140°F)	
Relative Humidity	4% ~ 100%	
Max. Operating Altitude	4,000 m (13,123 ft.)	
<b>Electrical</b>		
Input AC Voltage for Cabinet	100 V ~ 240 V, L / N (L) + PE	
Input AC Voltage for PID	380 V ~ 800 V, 3Ph + FE (Functional Earth)	
Input AC Voltage for PLC	380 V ~ 800 V, 3Ph	
Input AC Frequency	50 Hz / 60 Hz	
<b>Mechanical</b>		
Cable Entries	Bottom in & out	
Maintenance	Front	
Dimensions (W x H x D)	640 x 770 x 315 mm (25.2 x 30.3 x 12.4 inch)	880 x 770 x 369 mm (34.6 x 30.3 x 14.5 inch)
Weight	29 kg (63.9 lb.)	49 kg (108.0 lb.)
Protection Degree	Type 4X (without SmartPID2000 Module)	Type 3R (with SmartPID2000 Module)
Installation Options	Wall Mounting, Rack Mounting, Pole Mounting	

# SmartLogger2000



## Smart

- Functioning as communication manager, data logger, PLC master and Ethernet switch
- Multiple communication interfaces including PLC, RS485, Fast Ethernet, and SFP ports, flexible applications
- STP and RSTP supported for fiber ring network and ring protection
- Bluetooth, embedded WEB and USB supported, user-friendly
- Fast and reliable active and reactive power compensation control
- Smart I-V Curve Diagnosis supported

## Simple

- Up to 200 devices supported, including up to 150 inverters
- An integration of data collection, protocol conversion and Ethernet switch

## Reliable

- Industrial-level application and high reliability

Technical Specifications	SmartLogger2000
	<b>Device Management</b>
Max. Number of Manageable Devices	200
Max. Number of Manageable Smart Inverters	150
	<b>Communication Interface</b>
Electrical Ethernet	ETH x 2, 10 / 100 Mbps
Optical Ethernet (optional)	SFP x 2, 100 Mbps
RS485	COM x 6, 2400 / 4800 / 9600 / 19200 / 115200 bps
PLC	PLC x 1, 115.2 kbps
Digital / Analog Input / Output	DI x 8, DO x 3, AI x 7, AO x 4, PT100 / PT1000 x 2
	<b>Communication Protocol</b>
Ethernet	Modbus-TCP, IEC 60870-5-104
RS485	Modbus-RTU, IEC 60870-5-103 (standard), DL / T645
	<b>Interaction</b>
LED	LED Indicator x 4
WEB	Embedded WEB
Bluetooth	SUN2000 App
USB	USB 2.0 x 1
	<b>Environment</b>
Operating Temperature Range	-40°C ~ 60°C (-40°F ~ 140°F)
Storage Temperature Range	-40°C ~ 70°C (-40°F ~ 158°F)
Relative Humidity (Non-condensing)	5% ~ 95%
Max. Operating Altitude	4,000 m (13,123 ft.)
	<b>Electrical</b>
Power Supply	100 V ~ 240 V, 50 Hz / 60 Hz
Power Consumption	Typical 8 W, Max. 15 W
	<b>Mechanical</b>
Dimensions (W x H x D)	411 x 170 x 58.6 mm (16.2 x 6.7 x 2.3 inch)
Weight	2.5 kg (5.5 lb.)
Protection Degree	Type 1
Export Limitation	Supported
Installation Options	Wall Mounting, DIN Rail Mounting, Integrated Inside SmartACU2000B

The text and figures reflect the current technical state at the time of printing. Subject to technical changes. Errors and omissions excepted. Huawei assumes no liability for mistakes or printing errors. For more information, please visit solar.huawei.com. Version No.:01-(201808)