


SmartLogger 1000A



Smart

Smart zero export control design



Simple

2G / 3G / 4G communication¹



Reliable

Safety improvement by SPD inside

Technical Specification	SmartLogger 1000A
Device Management	
Max. Number of Connected Devices	80
Communication Interface	
Electrical Ethernet	ETH x 1, 10 / 100 Mbps
RS485	COM x 3, 2400 / 4800 / 9600 / 19200 / 115200 bps, 1000 m
MBUS (Optional)	Max. AC 800 V (±10%)
2G / 3G / 4G	LTE (FDD), DC-HSPA+ / HSPA+ / HSPA / UMTS, GSM / GPRS / EDGE ²
Digital / Analog Input / Output	DI x 4, DO x 2, AI x 4
Active DO	12V, 100mA (connection with relay, sensor)
SPD Inside	Yes
Communication Protocol	
Ethernet	Modbus-TCP, IEC 60870-5-104
RS485	Modbus-RTU, IEC 60870-5-103 (standard), DL / T645
Interaction	
LED	LED Indicator x 4 – RUN, ALM, 4G, WLAN
WEB	Embedded Web
USB	USB 2.0 x 1
APP	Communication by WLAN
Environment	
Operating Temperature Range	-40°C ~ 60°C (-40°F ~ 140°F)
Storage Temperature	-40°C ~ 70°C (-40°F ~ 158°F)
Relative Humidity (Non-condensing)	5% ~ 95%
Max. Operating Altitude	4,000 m (13,123 ft.)
Electrical	
AC Power Supply	100 V ~ 240 V, 50 Hz / 60 Hz
DC Power Supply	20 ~ 30 V
Power Consumption	Typical 8 W, Max. 15 W
General Data	
Dimensions (W x H x D)	200 x 140 x 53 mm (7.9 x 5.5 x 2.1 inch, without mounting ears and antenna)
Weight	2 kg (4.4 lb.)
Degree of Protection	IP20
Installation Options	Wall Mounting, DIN Rail Mounting, Tabletop Mounting

^{*1} When putting inside metal box, extended antenna will be needed.

^{*2} For recommended carriers list and details on supported frequencies, please contact local distributors.