

Smart Power Sensor



🎯 Accurate


- Measurement accuracy > class 1 within full temperature range

📄 Simple & Easy

- Standard din-rail mounting of DIN 35 mm
- Small volume, 1P2W 36 mm, 3P4W 72 mm
- LCD display, convenient for users to set and check
- Coupling connection for installation
- CT and RS485 cables included in accessories

✅ Energy-efficient

- Overall power consumption ≤ 1 W

Technical Specification	DDSU666-H	DTSU666-H
General Specification		
Dimension (H * W * D)	36 * 100 * 65.5mm (1.4 * 3.9 * 2.6 inch)	72 * 100 * 65.5 mm (2.8 * 3.9 * 2.6 inch)
Mounting type	DIN35 Rail	
Weight (including cables)	1.2 kg (2.6 lb)	1.5 kg (3.3 lb)
Power Supply		
Power grid type	1P2W	3P4W
Input power (phase voltage)	176 Vac ~ 288 Vac	
Power consumption	≤ 0.8W	≤ 1W
Measurement Range		
Line voltage	/	304 Vac ~ 499 Vac
Phase voltage	176 Vac ~ 288 Vac	
Current	0 ~ 100A	
Measurement Accuracy		
Voltage	± 0.5%	
Current / Power / Energy	± 1%	
Frequency	± 0.01Hz	
Communication		
Interface	RS485	
Baud rate	9,600 bps	
Communication protocol	Modbus-RTU	
Environment		
Operating temperature range	-25 °C ~ 60 °C	
Storage temperature range	-40 °C ~ 70 °C	
Operating humidity	5% ~ 95% (non-condensing)	
Others		
Accessories	RS485 Cable (10m / 33 ft.)	
	1 CT 100A / 40mA (6m / 19 ft.) 	3 CT 100A / 40mA (6m / 19 ft.) 