

SPMS2000

Smart Plant Management System



Comprehensive management

GW-level PV&ESS plant management
Multi-level refined management



Efficient collaboration

Power generation plan curve
Multi-energy scheduling



Intelligent diagnosis

Full-link multi-dimensional plant diagnosis
Cell/module fault pre-warning



Secure and reliable

IEC62443 certification.
Redundant design, high availability

*The product is without workstation devices

➤ Specifications

Parameter Type	Parameter Description		
Cabinet			
W x D x H	600mm×1200mm×2200mm (47u)	Weight	Net weight approx. 210 kg, full configuration approx. 600 kg
Temperature	5 - 30°C	Power Supply	200V~240V, 50/60Hz
Protection Grade	IP20	Certification	CB/CE, etc.
Altitude	≤4000m		
Server			
Model	TaiShan 200 (2280)	Hard Disk	8*1.92T SATA SSD
W x D x H	482.6mm*790mm*88.9mm. (2U)	Fans	Four hot-swappable fans in N+1 redundancy
CPU	2*Kunpeng 920 - 48core @2.6GHz	External Interface	8*GE
Database	GaussDB	Power supply	2 x 900 W, 1+1 Redundancy
Operating system	EulerOS	Net weight	Approx. 30 kg
Memory	4*64G	Certification	CCC/CE, etc.
Switch			
Model	CloudEngine S5735-S24ST4XE-V2		CloudEngine S5735-S24T4XE-V2
W x D x H	420mm*442mm*43.6mm (1U)		420mm*442mm*43.6mm (1U)
Net Weight	4.95 kg		4.34 kg
Memory	2 GB		2 GB
Power Supply	2*80W		2 x 80 W, 1+1 redundancy
Interface	Eight gigabit electrical ports, four 10GE optical ports, and 24 gigabit optical ports		24 GE electrical ports and 4 10GE optical ports
Rated Voltage	100V AC~240V AC; 50/60Hz		100V AC~240V AC; 50/60Hz
Certification	CE/VCCI, etc.		CCC/CE/RoHS, etc.