

► LUNA2000-4472-2S

Smart String ESS



All-architecture
Safety



All-scenario
Grid forming



All-lifecycle
Cost-effectiveness



All-rounder
Digitalization

Technical Specifications

Battery Container	
Model	LUNA2000-4472-2S
DC Rated Voltage	1,331.2V
DC Max. Voltage	1,500V
Nominal Energy Capacity	4,472 kWh
Charge & Discharge Rate	≤ 0.5 C
Rated Power	2,236 kW
Dimension (W x H x D)	6,058 x 2,896 x 2,438 mm
Weight	≤ 42 t
Operation Temperature Range	-30°C ~ 55°C
Storage Temperature Range	-40°C ~ 60°C
Relative Humidity	0 ~ 100% (Non-condensing)
Max. Operating Altitude	4,700 m
Cooling Method	Liquid Cooling
Fire Suppression System	Water Sprinkler, Novec 1230 (Optional)
Communication Interface	Ethernet / SFP
Communication Protocol	Modbus TCP
Protection Degree	IP55
Anti-corrosion Degree	C5-Medium
Standards Compliance	
RoHS, IEC62477-1, IEC62040-1, IEC61000-6-2, IEC62933-5-2, UL9540A, IEC62619, UN38.3, etc.	
Battery PACK	
Cell Material	LFP
Number of Cell	104
Nominal Capacity	280 Ah / 93.18 kWh
Protection Degree	IP65
Weight	670±10 kg
Dimensions (W x H x D)	785 x 249 x 2182 mm

► LUNA2000-5015 Series

Smart String ESS



All-architecture
Safety



All-scenario
Grid forming



All-lifecycle
Cost-effectiveness



All-rounder
Digitalization

Technical Specifications

Battery Container	
Model	LUNA2000-5015-2S
DC Rated Voltage	1,331.2V
DC Max. Voltage	1,500V
Nominal Energy Capacity	5,015 kWh
Charge & Discharge Rate	≤ 0.5 C
Rated Power	2,507 kW
Dimension (W x H x D)	6,058 x 2,896 x 2,438 mm
Weight	≤ 43 t
Operation Temperature Range	-30°C ~ 55°C
Storage Temperature Range	-35°C ~ 60°C (With Coolant) -40°C ~ 60°C (Without Coolant)
Relative Humidity	0 ~ 100% (Non-condensing)
Max. Operating Altitude	4,700 m
Cooling Method	Liquid Cooling
Fire Suppression System	Water Sprinkler, Novec 1230
Communication Interface	Ethernet / SFP
Communication Protocol	Modbus TCP
Protection Degree	IP55
Anti-corrosion Degree	C5-Medium
Standards Compliance	
RoHS, IEC62477-1, IEC62040-1, IEC61000-6-2, IEC62933-5-2, UL9540A, IEC62619, UN38.3, etc.	
Battery PACK	
Cell Material	LFP
Number of Cell	104
Nominal Capacity	314 Ah / 104.5 kWh
Protection Degree	IP65
Weight	≤ 710 kg
Dimensions (W x H x D)	785 x 249 x 2135 mm